


# TORNADO®

## 1800 X 25 X 1MM HEX NET



### Description

1800 x 25 x 1mm Hex Net offers an effective solution when constructing pheasant release pens. Pens are used for releasing both pheasants and partridges. Crucially they provide safety, especially from ground predators, while the birds acclimatise to life in the wild. In July or early August, six to eight-week old pheasant poults are usually placed into release pens where they remain from a few days up to six weeks before being let out to move freely between the pen and surrounding habitat. Additional protection using electric fencing is recommended.

### Installation Guidelines

The netting should be supported by three 2.5HT line wires positioned at the top, middle and bottom of the net. They should be tied off and joined using suitable joiners before being tensioned between the straining posts. A straining post is required at every major change in direction or any termination and should be supported by a strut or box assembly. Zinc and zinc aluminium coated agricultural fence service life can be affected significantly when exposed to extremely acidic / alkaline or saline environments and this factor should be considered when designing your fence installation. For typical service life to be achieved it is recommended that the product must be installed in an atmosphere with corrosion class C1, C2 or C3 (very low/low/ medium) in accordance with ISO 9223 and must not come into contact with substances that will accelerate corrosion,

including but not limited to fertilisers, pesticides, herbicides, salt water and soils of pH lower than 5.5. Particularly at sites with peaty and wet ground conditions it is recommended that you have the soil pH tested prior to designing your installation. For more information on installation please refer to BS1722 part 2.

### Suitable For

Game Management

### Specification

Wire Gauge (mm)	1
Overall Height (mm)	1800
Mesh Size (mm)	25
Approx. weight per 50m roll	47kg
Material Composition	Heavily galvanised steel wire

All measurements are approximate. It is the user's responsibility to check the product is suitable for the application. We reserve the right to change specifications without notification.

**TORNADO®**  
Latest update: 08/10/24

sales@tornadowire.com  
Tel: +44 (0) 1789 778 766



# TORNADO<sup>®</sup>

## 1800 X 25 X 1MM HEX NET

### British & European Standards

BSEN 10218	Steel Wire and Wire Products part 2 - General Wire Dimensions and Tolerances.
BSEN 10223	Steel Wire and Wire Products for Fencing and Netting part 5 - Steel Wire Woven Hinged Joint and Knotted Mesh Fencing.
BSEN 10244	Steel Wire and Wire Products Non-ferrous Metallic Coatings on Steel Wire part 2 - Zinc or Zinc Alloy Coatings (all Tornado products galvanised to class A).
BS EN ISO9001	Tornado Wire Ltd operates a quality management system certified to this standard.

### Sustainability

All Tornado products are 100% recyclable.

### Traceability

This fence is batch marked and can be traced back to point of manufacture.


### Health & Safety

It is recommended that safety gloves, boots and glasses are worn at all times when handling the product.

### Product Codes

50m roll HXST182500

Wire Gauge (mm) - 1



Mesh Size (mm) - 25

Tornado Wire Limited, Bidford-on-Avon, Alcester, Warwickshire, B50 4JH. Tel: +44 (0) 01789 778 766 | www.tornadowire.com | email: sales@tornadowire.com

**TORNADO<sup>®</sup>**  
Latest update: 08/10/24

sales@tornadowire.com  
Tel: +44 (0) 1789 778 766

