


TORNADO[®]

MHT8/80/30 STOCK FENCE



Description

MHT8/80/30 is a cost effective alternative to mild steel stock fencing, and the 30cm distance between the stay wires provides a more economical option than MHT Stock Fence with 15cm spacings. Tornado MHT is manufactured with high tensile wire which strains tighter than mild steel and so requires fewer intermediate posts, making it quicker to erect. The spring like properties of a high tensile wire help the netting stay tight, keeping maintenance to a minimum.

Installation Guidelines

A straining post is required at every major change in direction or any termination and should be supported by a strut or box assembly. Netting should be tied off on the straining posts by hand or with suitable joiners. When tensioning the fence the 'crimp' in the net should be reduced by approx: 50%. Avoid driving staples tight against the wire as this will damage the galvanised coating. Additional line wire can be added to the top of the fence for additional height. For more information on installation please refer to BS1722 part 2.

Suitable For

Sheep

Cattle

Specification

Number of line wires	8
Overall height	80cm
Distance between stay wires	30cm
Top & bottom line wire specification	2.24mm diameter - 1235 - 1390 N/mm ²
Intermediate line wire specification	2.24mm diameter - 1235 - 1390 N/mm ²
Vertical stay wire specification	2.24mm diameter - 695 - 850 N/mm ²
Approx. weight per 100m roll	37kg
Material composition	Heavily galvanised steel wire

All measurements are approximate. It is the user's responsibility to check the product is suitable for the application. We reserve the right to change specifications without notification.

TORNADO[®]
Latest update: 01/12/21

sales@tornadowire.com
Tel: +44 (0) 1789 778 766



TORNADO®

MHT8/80/30 STOCK FENCE

British & European Standards

- BS EN 10218** Steel Wire and Wire Products part 2 - General Wire Dimensions and Tolerances.
- BS EN 10223** Steel Wire and Wire Products for Fencing and Netting part 5 - Steel Wire Woven Hinged Joint and Knotted Mesh Fencing.
- BS EN 10244** Steel Wire and Wire Products Non-ferrous Metallic Coatings on Steel Wire part 2 - Zinc or Zinc Alloy Coatings (all Tornado products galvanised to class A).
- BS EN ISO9001** Tornado Wire Ltd operates a quality management system certified to this standard.

Sustainability

All Tornado products are 100% recyclable.

Traceability

This fence is batch marked and can be traced back to point of manufacture.


Health & Safety

It is recommended that safety gloves, boots and glasses are worn at all times when handling the product.

Product Codes

100m roll	HZMH088002
250m roll*	HZMH088004

*Minimum order quantity may apply.



Tornado Wire Limited, Bidford-on-Avon, Alcester, Warwickshire, B50 4JH. Tel: +44 (0) 01789 778 766 | www.tornadowire.com | email: sales@tornadowire.com

TORNADO®
Latest update: 01/12/21

sales@tornadowire.com
Tel: +44 (0) 1789 778 766

